



<b>Product Name :</b> Compact aluminum air cylinders																															
<b>Item No. :</b> CJ, CJD, CJN																															
<b>Description :</b> Product name: CJ, CJD, CJN Port size: M5, G1/8, G1/4, G3/8 Max. operating pressure: 1 ~ 9.9 kgf/cm <sup>2</sup> Material of cylinder barrel: Aluminium																															
<b>Features :</b>	<b>Operation</b>																														
	<b>Single and double acting</b>																														
	<table border="1"> <tr> <td>φ</td><td>φ</td><td>φ</td><td>φ</td><td>φ</td><td>φ</td><td>φ</td><td>φ</td><td>φ</td><td>φ</td> </tr> <tr> <td>Bore size (mm)</td><td>12</td><td>16</td><td>20</td><td>25</td><td>32</td><td>40</td><td>50</td><td>63</td><td>80</td><td>100</td> </tr> </table>										φ	φ	φ	φ	φ	φ	φ	φ	φ	φ	Bore size (mm)	12	16	20	25	32	40	50	63	80	100
	φ	φ	φ	φ	φ	φ	φ	φ	φ	φ																					
	Bore size (mm)	12	16	20	25	32	40	50	63	80	100																				
	Stroke 10,15,20,25,30,35,40,45,50,55,60,75,85,100(mm)																														
	Stroke range MAX.30      MAX.100 (mm)																														
Used fluid Filtered air with or without lubrication																															
Pressure range 1 ~ 9.9 kgf/cm <sup>2</sup>																															
The range of temperature -10 ~ +60 °C (No freezing)																															