



Product Name : Miniature stainless steel tube air cylinders																																																																																																																																																																																																											
Item No. : DIC, DIA, DID, SRI, SHI																																																																																																																																																																																																											
Description :	Product name: DIC, DIA, DID, SRI, SHI Port size: PT1/8, PT1/4 Max. operating pressure: 1 ~ 9.9 kgf/cm ² Max. supply pressure: 9.9 kgf/cm ²																																																																																																																																																																																																										
Features :	<table border="1"> <thead> <tr> <th>Operation</th> <th colspan="6">Single and double acting</th> </tr> </thead> <tbody> <tr> <td>Bore Diameter (mm)</td> <td>φ 12</td> <td>φ 16</td> <td>φ 20</td> <td>φ 25</td> <td>φ 32</td> <td>φ 40</td> </tr> <tr> <td>Standard stroke (mm)</td> <td colspan="6">15,25,50,75,100,125,150,200,250,300,400,500</td> </tr> <tr> <td>Used fluid</td> <td colspan="6">Filtered air with or without lubrication</td> </tr> <tr> <td>Barrel material</td> <td colspan="6">Stainless steel tube SUS 304</td> </tr> <tr> <td>Pressure range</td> <td colspan="6">1 ~ 9.9 kgf/cm²</td> </tr> <tr> <td>Temperature range</td> <td colspan="6">-10 ~ +60 °C (No freezing)</td> </tr> </tbody> </table> <p>1. These series air cylinder applicable bore dia. from φ 12 ~ φ 40mm meets with international interchangeable ISO 6432.</p> <p>2. With permanent magnetic ring(as a standard) .</p> <p>3. Cylinder cover cap are roller burnished onto the cylinder barrels so as to be pressure tight high concentricity good sealing and the cylinder provides longer life.</p> <p>4. With stainless steel #304 barrel material looks light and beauty never corroded and good thermo dispersion.</p> <p>5. All accessories available.</p>	Operation	Single and double acting						Bore Diameter (mm)	φ 12	φ 16	φ 20	φ 25	φ 32	φ 40	Standard stroke (mm)	15,25,50,75,100,125,150,200,250,300,400,500						Used fluid	Filtered air with or without lubrication						Barrel material	Stainless steel tube SUS 304						Pressure range	1 ~ 9.9 kgf/cm ²						Temperature range	-10 ~ +60 °C (No freezing)																																																																																																																																																														
Operation	Single and double acting																																																																																																																																																																																																										
Bore Diameter (mm)	φ 12	φ 16	φ 20	φ 25	φ 32	φ 40																																																																																																																																																																																																					
Standard stroke (mm)	15,25,50,75,100,125,150,200,250,300,400,500																																																																																																																																																																																																										
Used fluid	Filtered air with or without lubrication																																																																																																																																																																																																										
Barrel material	Stainless steel tube SUS 304																																																																																																																																																																																																										
Pressure range	1 ~ 9.9 kgf/cm ²																																																																																																																																																																																																										
Temperature range	-10 ~ +60 °C (No freezing)																																																																																																																																																																																																										
Other description :	<table border="1"> <thead> <tr> <th colspan="2"></th> <th colspan="11">Unit (m/m)</th> </tr> <tr> <th colspan="2">Bore Diameter</th> <th colspan="11">Standard Stroke</th> </tr> <tr> <th colspan="2"></th> <th>15</th> <th>25</th> <th>50</th> <th>75</th> <th>100</th> <th>125</th> <th>150</th> <th>200</th> <th>250</th> <th>300</th> <th>400</th> <th>500</th> </tr> </thead> <tbody> <tr> <td rowspan="2">φ 12</td> <td>Single</td> <td>●</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>Double</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td rowspan="2">φ 16</td> <td>Single</td> <td>●</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>Double</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td rowspan="2">φ 20</td> <td>Single</td> <td>—</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>Double</td> <td>—</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td rowspan="2">φ 25</td> <td>Single</td> <td>—</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>Double</td> <td>—</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td rowspan="2">φ 32</td> <td>Single</td> <td>—</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>Double</td> <td>—</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> </tr> <tr> <td rowspan="2">φ 40</td> <td>Single</td> <td>—</td> <td>●</td> <td>●</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>Double</td> <td>—</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> <td>●</td> </tr> </tbody> </table> <p>(●) Standard Stroke (—) Non-Standard Stroke on Request</p>			Unit (m/m)											Bore Diameter		Standard Stroke													15	25	50	75	100	125	150	200	250	300	400	500	φ 12	Single	●	●	●	—	—	—	—	—	—	—	—	—	Double	●	●	●	●	●	●	●	—	—	—	—	—	φ 16	Single	●	●	●	—	—	—	—	—	—	—	—	—	Double	●	●	●	●	●	●	●	—	—	—	—	—	φ 20	Single	—	●	●	—	—	—	—	—	—	—	—	—	Double	—	●	●	●	●	●	●	●	—	—	—	—	φ 25	Single	—	●	●	—	—	—	—	—	—	—	—	—	Double	—	●	●	●	●	●	●	●	●	—	—	—	φ 32	Single	—	●	●	—	—	—	—	—	—	—	—	—	Double	—	●	●	●	●	●	●	●	●	●	●	●	φ 40	Single	—	●	●	—	—	—	—	—	—	—	—	—	Double	—	●	●	●	●	●	●	●	●	●	●	●
		Unit (m/m)																																																																																																																																																																																																									
Bore Diameter		Standard Stroke																																																																																																																																																																																																									
		15	25	50	75	100	125	150	200	250	300	400	500																																																																																																																																																																																														
φ 12	Single	●	●	●	—	—	—	—	—	—	—	—	—																																																																																																																																																																																														
	Double	●	●	●	●	●	●	●	—	—	—	—	—																																																																																																																																																																																														
φ 16	Single	●	●	●	—	—	—	—	—	—	—	—	—																																																																																																																																																																																														
	Double	●	●	●	●	●	●	●	—	—	—	—	—																																																																																																																																																																																														
φ 20	Single	—	●	●	—	—	—	—	—	—	—	—	—																																																																																																																																																																																														
	Double	—	●	●	●	●	●	●	●	—	—	—	—																																																																																																																																																																																														
φ 25	Single	—	●	●	—	—	—	—	—	—	—	—	—																																																																																																																																																																																														
	Double	—	●	●	●	●	●	●	●	●	—	—	—																																																																																																																																																																																														
φ 32	Single	—	●	●	—	—	—	—	—	—	—	—	—																																																																																																																																																																																														
	Double	—	●	●	●	●	●	●	●	●	●	●	●																																																																																																																																																																																														
φ 40	Single	—	●	●	—	—	—	—	—	—	—	—	—																																																																																																																																																																																														
	Double	—	●	●	●	●	●	●	●	●	●	●	●																																																																																																																																																																																														



Product Name :	Accessories
Item No. :	FA, FB, LB, CB, TC, I, Y, P, KG
Description :	Bore Diameter (mm): (ϕ 12, ϕ 16, ϕ 20, ϕ 25, ϕ 32, ϕ 40)