



Product Name : Manual valve(1/8)		
Item No. : H-5-1/8		
Description :	Product name: H-5-1/8 Port size: G 1/8 Max. operating pressure: 1.5 ~ 8 kgf/cm <sup>2</sup> Max. supply pressure: 8 kgf/cm <sup>2</sup> ☆5/2 Manual valve.	
Features :	Port thread size	G 1/8
	Port amount	5 port/2 position (5/2)
	Used fluid	Air
	Pressure range	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)
	Nominal flow	650 NL/min
	Effective section area	12 mm <sup>2</sup>
	Ambient temperature	0 ~ 60 °C
	Weight	100 g



Product Name : Manual valve(1/4)		
Item No. : H-5-1/4		
Description :	Product name: H-5-1/4 Port size: G 1/4 Max. operating pressure: 1.5 ~ 8 kgf/cm <sup>2</sup> Max. supply pressure: 8 kgf/cm <sup>2</sup> ☆5/2 Manual valve.	
Features :	Port thread size	G 1/4
	Port amount	5 port/2 position (5/2)
	Used fluid	Air
	Pressure range	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)
	Nominal flow	945 NL/min
	Effective section area	18 mm <sup>2</sup>
	Ambient temperature	0 ~ 60 °C
	Weight	180 g



Product Name : Manual valve(1/8, 1/4)			
Item No. : PVH-152, PVH-252			
Description :	Product name: PVH-152, PVH-252		
	Port size: G 1/8, G 1/4		
	Max. operating pressure: 0 ~ 8 kgf/cm <sup>2</sup>		
	Max. supply pressure: 8 kgf/cm <sup>2</sup>		
	☆5/2 Manual valve.		
Features :	Port thread size	G 1/8	G 1/4
	Port amount	5 port/2 position (5/2)	
	Used fluid	Air	
	Pressure range	0 ~ 8 kgf/cm <sup>2</sup> (0 ~ 0.8 MPa)	
	Nominal flow	650 NL/min	945 NL/min
	Effective section area	12 mm <sup>2</sup>	18 mm <sup>2</sup>
	Ambient temperature	0 ~ 60 °C	
	Weight	100 g	180 g



Product Name : Pilot control valve			
Item No. : V-5-1/8(1/4), PVSP-152(252), PVSP-152(252)-T			
Description :	Product name: V-5-1/8(1/4), PVSP-152(252), PVSP-152(252)-T		
	Port size: G1/8, G1/4		
	Max. operating pressure: 1.5 ~ 8 kgf/cm <sup>2</sup>		
	Max. supply pressure: 10 kgf/cm <sup>2</sup>		
	☆5/2 Directional control valve. The pilot control valve have short action distance and small action force, no direction restricted for contact.		
Features :	Port thread size	G 1/8	G 1/4
	Port amount	5 port/2 position (5/2)	
	Used fluid	Air	
	Pressure range	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)	
	Effective section area	12 mm <sup>2</sup>	18 mm <sup>2</sup>
	Ambient temperature	0 ~ 60 °C	
	Weight	100 g	180 g



<b>Product Name :</b> Selector switch directional control valve(1/4)		
<b>Item No. :</b> F-3-1/4, F-4-1/4		
<b>Description :</b>	Product name: F-3-1/4, F-4-1/4 Port size: 1/4 Max. operating pressure: 0 ~ 7 kgf/cm <sup>2</sup> Max. supply pressure: 8 kgf/cm <sup>2</sup> ☆2/2, 3/2, 4/2 Selector switch directional control valve.	
<b>Features :</b>	<b>Port thread size</b>	G 1/4
	<b>Port amount</b>	(2/2, 3/2)                      (4/2)
	<b>Used fluid</b>	Air
	<b>Pressure range</b>	0 ~ 7 kgf/cm <sup>2</sup> (0 ~ 0.7 MPa)
	<b>Nominal flow</b>	600 NL/min
	<b>Ambient temperature</b>	0 ~ 60 °C
	<b>Weight</b>	360 g                      660 g