



Product Name : Pilot valve(1/8)																																							
Item No. : PV-152-S, PV-152-D, PV-153-D																																							
Description :	Product name: PV-152-S, PV-152-D, PV-153-D Port size: G1/8 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2(3)Pneumatically actuated valve.																																						
Features :	<table border="1"> <thead> <tr> <th>Model</th> <th>PV-152-S</th> <th>PV-152-D</th> <th>PV-153-D</th> </tr> </thead> <tbody> <tr> <td>Port thread size</td> <td colspan="3">G 1/8</td> </tr> <tr> <td>Port amount</td> <td colspan="2">Five port/Two position (5/2)</td> <td>Five port/Two position (5/3)</td> </tr> <tr> <td>Used fluid</td> <td colspan="3">Air</td> </tr> <tr> <td>Pressure range</td> <td colspan="2">1.5 ~ 8 kgf/cm²</td> <td>2 ~ 7 kgf/cm²</td> </tr> <tr> <td>Effective section area</td> <td colspan="2">12 mm²</td> <td>9 mm²</td> </tr> <tr> <td>Nominal flow</td> <td colspan="2">670 NL/min</td> <td>500 NL/min</td> </tr> <tr> <td>Ambient temperature</td> <td colspan="3">0 ~ 60 °C</td> </tr> <tr> <td>Ambient temperature</td> <td>60 g</td> <td>80 g</td> <td>100 g</td> </tr> </tbody> </table>			Model	PV-152-S	PV-152-D	PV-153-D	Port thread size	G 1/8			Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)	Used fluid	Air			Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²	Effective section area	12 mm ²		9 mm ²	Nominal flow	670 NL/min		500 NL/min	Ambient temperature	0 ~ 60 °C			Ambient temperature	60 g	80 g	100 g
Model	PV-152-S	PV-152-D	PV-153-D																																				
Port thread size	G 1/8																																						
Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)																																				
Used fluid	Air																																						
Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²																																				
Effective section area	12 mm ²		9 mm ²																																				
Nominal flow	670 NL/min		500 NL/min																																				
Ambient temperature	0 ~ 60 °C																																						
Ambient temperature	60 g	80 g	100 g																																				



Product Name : Pilot valve(1/4)																																							
Item No. : PV-252-S, PV-252-D, PV-253-D																																							
Description :	Product name: PV-252-S, PV-252-D, PV-253-D Port size: G1/4 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2(3)Pneumatically actuated valve.																																						
Features :	<table border="1"> <thead> <tr> <th>Model</th> <th>PV-252-S</th> <th>PV-252-D</th> <th>PV-253-D</th> </tr> </thead> <tbody> <tr> <td>Port thread size</td> <td colspan="3">G 1/4</td> </tr> <tr> <td>Port amount</td> <td colspan="2">Five port/Two position (5/2)</td> <td>Five port/Two position (5/3)</td> </tr> <tr> <td>Used fluid</td> <td colspan="3">Air</td> </tr> <tr> <td>Pressure range</td> <td colspan="2">1.5 ~ 8 kgf/cm²</td> <td>2 ~ 7 kgf/cm²</td> </tr> <tr> <td>Effective section area</td> <td colspan="2">18 mm²</td> <td>12 mm²</td> </tr> <tr> <td>Nominal flow</td> <td colspan="2">1000 NL/min</td> <td>700 NL/min</td> </tr> <tr> <td>Ambient temperature</td> <td colspan="3">0 ~ 60 °C</td> </tr> <tr> <td>Ambient temperature</td> <td>120 g</td> <td>140 g</td> <td>260 g</td> </tr> </tbody> </table>			Model	PV-252-S	PV-252-D	PV-253-D	Port thread size	G 1/4			Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)	Used fluid	Air			Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²	Effective section area	18 mm ²		12 mm ²	Nominal flow	1000 NL/min		700 NL/min	Ambient temperature	0 ~ 60 °C			Ambient temperature	120 g	140 g	260 g
Model	PV-252-S	PV-252-D	PV-253-D																																				
Port thread size	G 1/4																																						
Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)																																				
Used fluid	Air																																						
Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²																																				
Effective section area	18 mm ²		12 mm ²																																				
Nominal flow	1000 NL/min		700 NL/min																																				
Ambient temperature	0 ~ 60 °C																																						
Ambient temperature	120 g	140 g	260 g																																				



Product Name : Pilot valve(3/8)				
Item No. : PV-352-S, PV-352-D, PV-353-D				
Description :	Product name: PV-352-S, PV-352-D, PV-353-D Port size: G3/8 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2(3)Pneumatically actuated valve.			
Features :	Model	PV-352-S	PV-352-D	PV-353-D
	Port thread size	G 3/8		
	Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)
	Used fluid	Air		
	Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²
	Effective section area	30 mm ²		18 mm ²
	Nominal flow	1680 NL/min		1000 NL/min
	Ambient temperature	0 ~ 60 °C		
	Ambient temperature	220 g	220 g	380 g



Product Name : Pilot valve(1/2)				
Item No. : PV-452-S, PV-452-D, PV-453-D				
Description :	Product name: PV-452-S, PV-452-D, PV-453-D Port size: G1/2 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 10 kgf/cm ² ☆5/2(3)Pneumatically actuated valve.			
Features :	Model	PV-452-S	PV-452-D	PV-453-D
	Port thread size	G 1/2		
	Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)
	Used fluid	Air		
	Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²
	Effective section area	50 mm ²		30 mm ²
	Nominal flow	2790 NL/min		1680 NL/min
	Ambient temperature	0 ~ 60 °C		
	Ambient temperature	460 g	460 g	480 g