



Product Name : Solenoid valve (Direct operated type)(G1/8)																									
Item No. : PV-1321																									
Description :	Product name: PV-1321 Port size: G1/8 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 8 kgf/cm ²																								
Features :	<table border="1"> <tr> <td>Model</td> <td>PV-1321</td> </tr> <tr> <td>Port thread size</td> <td>G 1/8</td> </tr> <tr> <td>Port amount</td> <td>Three port/Two position(3/2)</td> </tr> <tr> <td>Used fluid</td> <td>Air</td> </tr> <tr> <td>Pressure range</td> <td>0 ~ 8 kgf/cm² (0 ~ 0.8 MPa)</td> </tr> <tr> <td>Effective section area</td> <td>1.54 mm²</td> </tr> <tr> <td>Nominal flow</td> <td>86 NL/min</td> </tr> <tr> <td>Ambient temperature</td> <td>0 ~ 60 °C</td> </tr> <tr> <td>Allowance voltage range</td> <td>AC110V, 220V(50/60) Hz, DC24V(±10%)</td> </tr> <tr> <td>Power consumption</td> <td>AC = 8VA, DC = 5W</td> </tr> <tr> <td>Insulation grade</td> <td>Class F</td> </tr> <tr> <td>Weight</td> <td>140 g</td> </tr> </table> <p>☆3/2Electrical solenoid valve, Directly actuated, European imported coil wire with low electricity consumption.</p>	Model	PV-1321	Port thread size	G 1/8	Port amount	Three port/Two position(3/2)	Used fluid	Air	Pressure range	0 ~ 8 kgf/cm ² (0 ~ 0.8 MPa)	Effective section area	1.54 mm ²	Nominal flow	86 NL/min	Ambient temperature	0 ~ 60 °C	Allowance voltage range	AC110V, 220V(50/60) Hz, DC24V(±10%)	Power consumption	AC = 8VA, DC = 5W	Insulation grade	Class F	Weight	140 g
Model	PV-1321																								
Port thread size	G 1/8																								
Port amount	Three port/Two position(3/2)																								
Used fluid	Air																								
Pressure range	0 ~ 8 kgf/cm ² (0 ~ 0.8 MPa)																								
Effective section area	1.54 mm ²																								
Nominal flow	86 NL/min																								
Ambient temperature	0 ~ 60 °C																								
Allowance voltage range	AC110V, 220V(50/60) Hz, DC24V(±10%)																								
Power consumption	AC = 8VA, DC = 5W																								
Insulation grade	Class F																								
Weight	140 g																								



Product Name : Solenoid valve(1/8)				
Item No. : PV-1521, PV-1522, PV-1532.42				
Description : Product name: PV-1521, PV-1522, PV-1532.42 Port size: G1/8 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 8 kgf/cm ²				
Features :	Model	PV-1521	PV-1522	PV-1532.42
	Port thread size	G 1/8		
	Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)
	Used fluid	Air		
	Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²
	Effective section area	12 mm ²		9 mm ²
	Nominal flow	670 NL/min		500 NL/min
	Ambient temperature	0 ~ 60 °C		
	Allowance voltage range	AC110V, 220V(50/60) Hz, DC24V(±10%)		
	Power consumption	AC = 3.5VA, DC = 2.4W		
	Insulation grade	Class F		
	Ambient temperature	120 g	175 g	200 g
	☆5/2(3)Electrical solenoid valve, Pneumatic and spring return, European imported coil wire with low electricity consumption.			



Product Name : Solenoid valve(1/4)				
Item No. : PV-2521, PV-2522, PV-2532.42				
Description : Product name: PV-2521, PV-2522, PV-2532.42 Port size: G1/4 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 8 kgf/cm ²				
Features :	Model	PV-2521	PV-2522	PV-2532.42
	Port thread size	G 1/4		
	Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)
	Used fluid	Air		
	Pressure range	1.5 ~ 8 kgf/cm ²	2 ~ 7 kgf/cm ²	
	Effective section area	18 mm ²	12 mm ²	
	Nominal flow	1000 NL/min	700 NL/min	
	Ambient temperature	0 ~ 60 °C		
	Allowance voltage range	AC110V, 220V(50/60) Hz, DC24V(±10%)		
	Power consumption	AC = 8VA, DC = 5W		
	Insulation grade	Class F		
	Weight	210 g	310 g	420 g
☆5/2(3)Electrical solenoid valve, Pneumatic and spring return, European imported coil wire with low electricity consumption.				



Product Name : Solenoid valve(3/8)				
Item No. : PV-3521, PV-3522, PV-3532.42				
Description :	Product name: PV-3521, PV-3522, PV-3532.42 Port size: G3/8 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 8 kgf/cm ²			
Features :	Model	PV-3521	PV-3522	PV-3532.42
	Port thread size	G 3/8		
	Port amount	Five port/Two position (5/2)		Five port/Two position (5/3)
	Used fluid	Air		
	Pressure range	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²
	Effective section area	30 mm ²		18 mm ²
	Nominal flow	1680 NL/min		1000 NL/min
	Ambient temperature	0 ~ 60 °C		
	Allowance voltage range	AC110V, 220V(50/60) Hz, DC24V(±10%)		
	Power consumption	AC = 8VA, DC = 5W		
	Insulation grade	Class F		
	Ambient temperature	300 g	385 g	525 g
☆5/2(3)Electrical solenoid valve, Pneumatic and spring return, European imported coil wire with low electricity consumption.				



Product Name : Solenoid valve(1/2)			
Item No. : PV-4521, PV-4522, PV-4532.42			
Description :	Product name: PV-4521, PV-4522, PV-4532.42 Port size: G1/2 Max. operating pressure: 0 ~ 8 kgf/cm ² Max. supply pressure: 8 kgf/cm ²		
Features :	Model	PV-4521	PV-4522
			PV-4532.42
	Port thread size	G 1/2	
	Port amount	Five port/Two position (5/2)	Five port/Two position (5/3)
	Used fluid	Air	
	Pressure range	1.5 ~ 8 kgf/cm ²	2 ~ 7 kgf/cm ²
	Effective section area	50 mm ²	30 mm ²
	Nominal flow	2790 NL/min	1680 NL/min
	Ambient temperature	0 ~ 60 °C	
	Allowance voltage range	AC110V, 220V(50/60) Hz, DC24V(±10%)	
	Power consumption	AC = 8VA, DC = 5W	
	Insulation grade	Class F	
	Ambient temperature	590 g	770 g
			770 g
☆5/2(3)Electrical solenoid valve, Pneumatic and spring return, European imported coil wire with low electricity consumption.			