

电磁阀 (G1/8)



产品名称 : 电磁阀(G1/8)																													
产品型号 : PV-150 系列																													
产品介绍 : 产品型号: PV-1521, PV-1522, PV-1532.42 配管口径尺寸: G1/8 使用压力范围: 0 ~ 8 kgf/cm ² 最大耐用压力: 8 kgf/cm ² 5/2(3)电磁阀, 五口二(三)位置, 线圈采用欧洲进口, 耗电量低。																													
详细规格 :	型号	PV-1521	PV-1522	PV-1532.42																									
	接管口径	G 1/8																											
	位置数	五口二位(5/2)		五口三位(5/3)																									
	使用流体	空气																											
	压力范围	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²																									
	有效断面积	12 mm ²		9 mm ²																									
	通称流量	670 NL/min		500 NL/min																									
	使用温度	0 ~ 60 °C																											
	容许电压范围	AC110V, 220V(50/60) Hz, DC24V(±10%)																											
	消耗电力	AC = 3.5VA, DC = 2.4W																											
	绝缘等级	F 级																											
	重量	120 g	175 g	200 g																									
订购标示 :	<div style="text-align: center;"> <p>訂購標示</p> <p>PV-1 5 2 1-M-L</p> <p>↓ ↓ ↓ ↓ ↓ ↓ ↓</p> <p>① ② ③ ④ ⑤ ⑥ ⑦</p> </div> <div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> <p>① 型式</p> <p>② 口径</p> <p>③ 方口数</p> </div> <div style="width: 30%;"> <p>④ 位置数</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 20px;">2</td> <td style="width: 50px;">二位置</td> <td></td> </tr> <tr> <td>3</td> <td>三位置 中間/關閉</td> <td></td> </tr> <tr> <td>4</td> <td>三位置 中間/開放</td> <td></td> </tr> </table> <p>⑤ 線圈數</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 20px;">1</td> <td>單線圈</td> </tr> <tr> <td>2</td> <td>雙線圈</td> </tr> </table> </div> <div style="width: 30%;"> <p>⑥ 電壓</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 20px;">M</td> <td>AC220V⁵⁰/₆₀HZ</td> </tr> <tr> <td>F</td> <td>AC110V⁵⁰/₆₀HZ</td> </tr> <tr> <td>B</td> <td>DC24V</td> </tr> </table> <p>⑦ 線圈型狀</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 20px;"></td> <td>出線型</td> </tr> <tr> <td>X</td> <td>接線盒</td> </tr> <tr> <td>L</td> <td>附燈LED</td> </tr> </table> </div> </div>				2	二位置		3	三位置 中間/關閉		4	三位置 中間/開放		1	單線圈	2	雙線圈	M	AC220V ⁵⁰ / ₆₀ HZ	F	AC110V ⁵⁰ / ₆₀ HZ	B	DC24V		出線型	X	接線盒	L	附燈LED
2	二位置																												
3	三位置 中間/關閉																												
4	三位置 中間/開放																												
1	單線圈																												
2	雙線圈																												
M	AC220V ⁵⁰ / ₆₀ HZ																												
F	AC110V ⁵⁰ / ₆₀ HZ																												
B	DC24V																												
	出線型																												
X	接線盒																												
L	附燈LED																												

电磁阀 (G1/4)



产品名称：电磁阀(G1/4)																			
产品型号：PV-250 系列																			
产品介绍：产品型号：PV-2521, PV-2522, PV-2532.42 配管口径尺寸：G1/4 使用压力范围：0 ~ 8 kgf/cm2 最大耐用压力：8 kgf/cm2 5/2(3)电磁阀，五口二(三)位置，线圈采用欧洲进口，耗电量低。																			
详细规格：	型号	PV-2521	PV-2522	PV-2532.42															
	接管口径	G 1/4																	
	位置数	五口二位(5/2)		五口三位(5/3)															
	使用流体	空气																	
	压力范围	1.5 ~ 8 kgf/cm2		2 ~ 7 kgf/cm2															
	有效断面积	18 mm2		12 mm2															
	通称流量	1000 NL/min		700 NL/min															
	使用温度	0 ~ 60 °C																	
	容许电压范围	AC110V, 220V(50/60) Hz, DC24V(±10%)																	
	消耗电力	AC = 8VA, DC = 5W																	
	绝缘等级	F 级																	
	重量	210 g	310 g	420 g															
订购标示：																			
訂購標示																			
PV-2 5 2 1-M-L																			
1 型式		4 位置數		6 電壓															
2 口徑		5 線圈數		7 線圈型狀															
3 方口數		<table border="1"> <tr> <td>2</td> <td>二位置</td> <td></td> </tr> <tr> <td>3</td> <td>三位置 中間/關閉</td> <td></td> </tr> <tr> <td>4</td> <td>三位置 中間/開放</td> <td></td> </tr> </table>		2	二位置		3	三位置 中間/關閉		4	三位置 中間/開放		<table border="1"> <tr> <td>M</td> <td>AC220V⁵⁰/₆₀ HZ</td> </tr> <tr> <td>F</td> <td>AC110V⁵⁰/₆₀ HZ</td> </tr> <tr> <td>B</td> <td>DC24V</td> </tr> </table>	M	AC220V ⁵⁰ / ₆₀ HZ	F	AC110V ⁵⁰ / ₆₀ HZ	B	DC24V
2	二位置																		
3	三位置 中間/關閉																		
4	三位置 中間/開放																		
M	AC220V ⁵⁰ / ₆₀ HZ																		
F	AC110V ⁵⁰ / ₆₀ HZ																		
B	DC24V																		
		<table border="1"> <tr> <td>1</td> <td>單線圈</td> </tr> <tr> <td>2</td> <td>雙線圈</td> </tr> </table>		1	單線圈	2	雙線圈	<table border="1"> <tr> <td></td> <td>出線型</td> </tr> <tr> <td>X</td> <td>接線盒</td> </tr> <tr> <td>L</td> <td>附燈LED</td> </tr> </table>		出線型	X	接線盒	L	附燈LED					
1	單線圈																		
2	雙線圈																		
	出線型																		
X	接線盒																		
L	附燈LED																		

电磁阀 (G3/8)



产品名称：电磁阀(G3/8)

产品型号：PV-350 系列

产品介绍：产品型号：PV-3521, PV-3522, PV-3532.42

配管口径尺寸：G3/8

使用压力范围：0 ~ 8 kgf/cm²


最大耐用压力：8 kgf/cm²

5/2(3)电磁阀，气压及弹簧回位，线圈采用欧洲进口，耗电量低。

详细规格：	型号	PV-3521	PV-3522	PV-3532.42
接管口径		G 3/8		
位置数		五口二位(5/2)		五口三位(5/3)
使用流体		空气		
压力范围		1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²
有效断面积		30 mm ²		18 mm ²
通用流体		1680 NL/min		1000 NL/min
使用温度		0 ~ 60 °C		
容许电压范围		AC110V, 220V(50/60) Hz, DC24V(±10%)		
消耗电力		AC = 8VA, DC = 5W		
绝缘等级		F 级		
重量		300 g	385 g	525 g

订购标示：**訂購標示**

PV-3 5 2 1-M-L



1 型式

2 口径

3 方口数

4 位置数

2	二位置	
3	三位置 中间/关闭	
4	三位置 中间/开放	

5 线圈数

1	单线圈
2	双线圈

6 电压

M	AC220V ⁵⁰ /60HZ
F	AC110V ⁵⁰ /60HZ
B	DC24V

7 线圈形状

	出线型
X	接线盒
L	附灯LED

电磁阀 (G1/2)



产品名称 :	电磁阀(G1/2)																												
产品型号 :	PV-450 系列																												
产品介绍 :	产品型号: PV-4521, PV-4522, PV-4532.42 配管口径尺寸: G1/2 使用压力范围: 0 ~ 8 kgf/cm ² 最大耐用压力: 8 kgf/cm ² 5/2(3)电磁阀, 气压及弹簧回位, 线圈采用欧洲进口, 耗电量低。																												
详细规格 :	型号	PV-4521	PV-4522	PV-4532.42																									
	接管口径	G 1/2																											
	位置数	五口二位(5/2)		五口三位(5/3)																									
	使用流体	空气																											
	压力范围	1.5 ~ 8 kgf/cm ²		2 ~ 7 kgf/cm ²																									
	有效断面积	50 mm ²		30 mm ²																									
	通用流体	2790 NL/min		1680 NL/min																									
	使用温度	0 ~ 60 °C																											
	容许电压范围	AC110V, 220V(50/60) Hz, DC24V(±10%)																											
	消耗电力	AC = 8VA, DC = 5W																											
	绝缘等级	F 级																											
	重量	590 g	770 g	770 g																									
订购标示 :	<div style="text-align: center;"> <p>訂購標示</p> <p>PV-4 5 2 1-M-L</p> <p>↓ ↓ ↓ ↓ ↓ ↓ ↓</p> <p>① ② ③ ④ ⑤ ⑥ ⑦</p> </div> <div style="display: flex; justify-content: space-between;"> <div style="width: 30%;"> <p>① 型式</p> <p>② 口径</p> <p>③ 方口数</p> </div> <div style="width: 30%;"> <p>④ 位置数</p> <table border="1" style="width: 100%;"> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">二位置</td> <td></td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">三位置 中間/關閉</td> <td></td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">三位置 中間/開放</td> <td></td> </tr> </table> <p>⑤ 線圈數</p> <table border="1" style="width: 100%;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">單線圈</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">雙線圈</td> </tr> </table> </div> <div style="width: 30%;"> <p>⑥ 電壓</p> <table border="1" style="width: 100%;"> <tr> <td style="text-align: center;">M</td> <td style="text-align: center;">AC220V⁵⁰/₆₀Hz</td> </tr> <tr> <td style="text-align: center;">F</td> <td style="text-align: center;">AC110V⁵⁰/₆₀Hz</td> </tr> <tr> <td style="text-align: center;">B</td> <td style="text-align: center;">DC24V</td> </tr> </table> <p>⑦ 線圈型狀</p> <table border="1" style="width: 100%;"> <tr> <td style="text-align: center;"> </td> <td style="text-align: center;">出線型</td> </tr> <tr> <td style="text-align: center;">X</td> <td style="text-align: center;">接線盒</td> </tr> <tr> <td style="text-align: center;">L</td> <td style="text-align: center;">附燈LED</td> </tr> </table> </div> </div>				2	二位置		3	三位置 中間/關閉		4	三位置 中間/開放		1	單線圈	2	雙線圈	M	AC220V ⁵⁰ / ₆₀ Hz	F	AC110V ⁵⁰ / ₆₀ Hz	B	DC24V		出線型	X	接線盒	L	附燈LED
2	二位置																												
3	三位置 中間/關閉																												
4	三位置 中間/開放																												
1	單線圈																												
2	雙線圈																												
M	AC220V ⁵⁰ / ₆₀ Hz																												
F	AC110V ⁵⁰ / ₆₀ Hz																												
B	DC24V																												
	出線型																												
X	接線盒																												
L	附燈LED																												