

## 手钮开关头部



产品名称：	手钮开关头部
产品型号：	H-S, P-F, P-M, P-L
产品介绍：	产品型号：H-S, P-F, P-M, P-L ☆手钮开关头部可以单独购买，其中 P-L、P-K 型之头部材质为塑料。

## 手钮作动阀 (M5)



产品名称：	手钮作动阀(M5)															
产品型号：	H-3-M5-S-2-22															
产品介绍：	产品型号：H-3-M5-S-2-22 配管口径尺寸：M5 使用压力范围：0 ~ 9.9 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆2(3)/2 滚轮作动阀，二(三)口二位置。															
详细规格：	接管口径	M5														
	位置数	二(三)口二位 (2/2, 3/2)														
	使用流体	空气														
	压力范围	0 ~ 9.9 kgf/cm <sup>2</sup> (0 ~ 0.99 MPa)														
	最大流量	110 NL/min														
	使用温度	0 ~ 60 °C														
	重量	180 g														
订购标示：	<div style="text-align: center;"> <p><b>訂購標示</b></p> <p><b>H-3-M5-S-2-22</b></p> <p>1 2 3 4 5 6</p> </div> <div style="display: flex; justify-content: space-around;"> <div style="width: 30%;"> <p>1 型式</p> <p>2 方口數</p> <p>3 口径</p> </div> <div style="width: 30%;"> <p>4 頭部型狀</p> <table border="1" style="width: 100%;"> <tr> <td>S</td> <td>短柄</td> <td></td> </tr> <tr> <td>L</td> <td>長柄</td> <td></td> </tr> </table> </div> <div style="width: 30%;"> <p>5 顏色</p> <table border="1" style="width: 100%;"> <tr> <td>2</td> <td>黑</td> </tr> <tr> <td>3</td> <td>綠</td> </tr> <tr> <td>4</td> <td>紅</td> </tr> </table> <p>6 安裝直徑</p> <table border="1" style="width: 100%;"> <tr> <td>φ 22</td> </tr> <tr> <td>φ 30</td> </tr> </table> </div> </div>		S	短柄		L	長柄		2	黑	3	綠	4	紅	φ 22	φ 30
S	短柄															
L	長柄															
2	黑															
3	綠															
4	紅															
φ 22																
φ 30																

# 手鈕作動閥 (M5)



产品名称：手鈕作動閥(M5)																													
产品型号：P-3-M5-F-2-22																													
产品介绍：产品型号：P-3-M5-F-2-22 配管口径尺寸：M5 使用压力范围：0 ~ 9.9 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆2(3)/2 滾輪作動閥，二(三)口二位置。																													
详细规格：	<table border="1"> <tr> <td>接管口径</td> <td>M5</td> </tr> <tr> <td>位置数</td> <td>二(三)口二位 (2/2, 3/2)</td> </tr> <tr> <td>使用流体</td> <td>空气</td> </tr> <tr> <td>压力范围</td> <td>0 ~ 9.9 kgf/cm<sup>2</sup> (0 ~ 0.99 MPa)</td> </tr> <tr> <td>最大流量</td> <td>110 NL/min</td> </tr> <tr> <td>使用温度</td> <td>0 ~ 60 °C</td> </tr> <tr> <td>重量</td> <td>180 g</td> </tr> </table>	接管口径	M5	位置数	二(三)口二位 (2/2, 3/2)	使用流体	空气	压力范围	0 ~ 9.9 kgf/cm <sup>2</sup> (0 ~ 0.99 MPa)	最大流量	110 NL/min	使用温度	0 ~ 60 °C	重量	180 g														
接管口径	M5																												
位置数	二(三)口二位 (2/2, 3/2)																												
使用流体	空气																												
压力范围	0 ~ 9.9 kgf/cm <sup>2</sup> (0 ~ 0.99 MPa)																												
最大流量	110 NL/min																												
使用温度	0 ~ 60 °C																												
重量	180 g																												
订购标示：	<div style="text-align: center;"> <p><b>訂購標示</b></p> <p><b>P-3-M5-F-2-22</b></p> <p>1 2 3 4 5 6</p> </div> <div style="display: flex; justify-content: space-around;"> <div style="width: 30%;"> <p><b>1 型式</b></p> <p><b>2 方口數</b></p> <p><b>3 口徑</b></p> </div> <div style="width: 30%;"> <p><b>4 頭部型狀</b></p> <table border="1"> <tr> <td>F</td> <td>平頭</td> <td></td> </tr> <tr> <td>P</td> <td>凸頭</td> <td></td> </tr> <tr> <td>M</td> <td>蘑菇</td> <td></td> </tr> <tr> <td>MX</td> <td>大蘑菇</td> <td></td> </tr> <tr> <td>L</td> <td>有停駐</td> <td></td> </tr> <tr> <td>K</td> <td>有停駐及鎖</td> <td></td> </tr> </table> <p>註：L、K型之頭部材質為塑膠</p> </div> <div style="width: 30%;"> <p><b>5 顏色</b></p> <table border="1"> <tr> <td>2</td> <td>黑</td> </tr> <tr> <td>3</td> <td>綠</td> </tr> <tr> <td>4</td> <td>紅</td> </tr> <tr> <td>6</td> <td>藍</td> </tr> </table> <p><b>6 安裝直徑</b></p> <table border="1"> <tr> <td>φ 22</td> </tr> <tr> <td>φ 30</td> </tr> </table> </div> </div>	F	平頭		P	凸頭		M	蘑菇		MX	大蘑菇		L	有停駐		K	有停駐及鎖		2	黑	3	綠	4	紅	6	藍	φ 22	φ 30
F	平頭																												
P	凸頭																												
M	蘑菇																												
MX	大蘑菇																												
L	有停駐																												
K	有停駐及鎖																												
2	黑																												
3	綠																												
4	紅																												
6	藍																												
φ 22																													
φ 30																													

# 手鈕作動閥 (1/8)



产品名称：手鈕作動閥(1/8)															
产品型号：H-3-1/8-S-2-22															
产品介绍：产品型号：H-3-1/8-S-2-22 配管口径尺寸：G1/8 使用压力范围：0 ~ 9.9 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆2(3)/2 滚轮作動閥，二(三)口二位置。															
详细规格：	接管口径	G 1/8													
	位置数	二(三)口二位 (2/2, 3/2)													
	使用流体	空气													
	压力范围	0 ~ 9.9 kgf/cm <sup>2</sup> (0 ~ 0.99 MPa)													
	最大流量	NC: 300 NL/min, NO: 320 NL/min													
	使用温度	0 ~ 60 °C													
	重量	180 g													
订购标示：	<div style="text-align: center;"> <p><b>訂購標示</b></p> <p><b>H-3-1/8-S-2-22</b></p> <p>                                                                1 2 3 4 5 6                 </p> </div> <div style="display: flex; justify-content: space-around; margin-top: 20px;"> <div style="width: 30%;"> <p>1 型式</p> <p>2 方口數</p> <p>3 口徑</p> </div> <div style="width: 30%;"> <p>4 頭部型狀</p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td style="width: 30px;">S</td> <td style="width: 60px;">短柄</td> <td></td> </tr> <tr> <td>L</td> <td>長柄</td> <td></td> </tr> </table> </div> <div style="width: 30%;"> <p>5 顏色</p> <table border="1" style="width: 100%; text-align: center;"> <tr><td style="width: 30px;">2</td><td>黑</td></tr> <tr><td>3</td><td>綠</td></tr> <tr><td>4</td><td>紅</td></tr> </table> <p>6 安裝直徑</p> <table border="1" style="width: 100%; text-align: center;"> <tr><td style="width: 30px;">φ 22</td></tr> <tr><td>φ 30</td></tr> </table> </div> </div>	S	短柄		L	長柄		2	黑	3	綠	4	紅	φ 22	φ 30
S	短柄														
L	長柄														
2	黑														
3	綠														
4	紅														
φ 22															
φ 30															

# 手鈕作動閥 (1/8)



<b>产品名称：</b> 手鈕作動閥(1/8)																			
<b>产品型号：</b> P-3-1/8-F-2-22																			
<b>产品介绍：</b> 产品型号：P-3-1/8-F-2-22 配管口径尺寸：G1/8 使用压力范围：0 ~ 9.9 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆2(3)/2 滾輪作動閥，二(三)口二位置。																			
<b>详细规格：</b>	<table border="1"> <tr> <td>接管口径</td> <td>G 1/8</td> </tr> <tr> <td>位置数</td> <td>二(三)口二位 (2/2, 3/2)</td> </tr> <tr> <td>使用流体</td> <td>空气</td> </tr> <tr> <td>压力范围</td> <td>0 ~ 9.9 kgf/cm<sup>2</sup> (0 ~ 0.99 MPa)</td> </tr> <tr> <td>最大流量</td> <td>NC: 300 NL/min, NO: 320 NL/min</td> </tr> <tr> <td>使用温度</td> <td>0 ~ 60 °C</td> </tr> <tr> <td>重量</td> <td>180 g</td> </tr> </table>	接管口径	G 1/8	位置数	二(三)口二位 (2/2, 3/2)	使用流体	空气	压力范围	0 ~ 9.9 kgf/cm <sup>2</sup> (0 ~ 0.99 MPa)	最大流量	NC: 300 NL/min, NO: 320 NL/min	使用温度	0 ~ 60 °C	重量	180 g				
	接管口径	G 1/8																	
	位置数	二(三)口二位 (2/2, 3/2)																	
	使用流体	空气																	
	压力范围	0 ~ 9.9 kgf/cm <sup>2</sup> (0 ~ 0.99 MPa)																	
	最大流量	NC: 300 NL/min, NO: 320 NL/min																	
	使用温度	0 ~ 60 °C																	
	重量	180 g																	
<b>订购标示：</b>																			
<b>訂購標示</b>																			
<b>P-3-1/8-F-2-22</b>																			
<b>1 型式</b> <b>2 方口數</b> <b>3 口徑</b>	<b>4 頭部型狀</b> <table border="1"> <tr> <td>F</td> <td>平頭</td> <td></td> </tr> <tr> <td>P</td> <td>凸頭</td> <td></td> </tr> <tr> <td>M</td> <td>蘑菇</td> <td></td> </tr> <tr> <td>MX</td> <td>大蘑菇</td> <td></td> </tr> <tr> <td>L</td> <td>有停駐</td> <td></td> </tr> <tr> <td>K</td> <td>有停駐及鎖</td> <td></td> </tr> </table>	F	平頭		P	凸頭		M	蘑菇		MX	大蘑菇		L	有停駐		K	有停駐及鎖	
F	平頭																		
P	凸頭																		
M	蘑菇																		
MX	大蘑菇																		
L	有停駐																		
K	有停駐及鎖																		
	<b>5 顏色</b> <table border="1"> <tr> <td>2</td> <td>黑</td> </tr> <tr> <td>3</td> <td>綠</td> </tr> <tr> <td>4</td> <td>紅</td> </tr> <tr> <td>6</td> <td>藍</td> </tr> </table>	2	黑	3	綠	4	紅	6	藍										
2	黑																		
3	綠																		
4	紅																		
6	藍																		
	<b>6 安裝直徑</b> <table border="1"> <tr> <td>φ 22</td> </tr> <tr> <td>φ 30</td> </tr> </table>	φ 22	φ 30																
φ 22																			
φ 30																			
註：L、K型之頭部材質為塑膠																			

# 手鈕作動閥 (G1/4)



<b>产品名称：</b> 手鈕作動閥(G1/4)															
<b>产品型号：</b> H-5-1/4-S-2-22															
<b>产品介绍：</b> 产品型号：H-5-1/4-S-2-22 配管口径尺寸：G1/4 使用压力范围：1.5 ~ 8 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆5/2 滾輪作動閥，五口二位置。															
<b>详细规格：</b>	<table border="1"> <tr> <td>接管口径</td> <td>G 1/4</td> </tr> <tr> <td>位置数</td> <td>五口二位 (5/2)</td> </tr> <tr> <td>使用流体</td> <td>空气</td> </tr> <tr> <td>压力范围</td> <td>1.5 ~ 8 kgf/cm<sup>2</sup> (0.15 ~ 0.8 MPa)</td> </tr> <tr> <td>有效断面积</td> <td>18 mm<sup>2</sup></td> </tr> <tr> <td>使用温度</td> <td>0 ~ 60 °C</td> </tr> <tr> <td>重量</td> <td>300 g</td> </tr> </table>	接管口径	G 1/4	位置数	五口二位 (5/2)	使用流体	空气	压力范围	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)	有效断面积	18 mm <sup>2</sup>	使用温度	0 ~ 60 °C	重量	300 g
	接管口径	G 1/4													
	位置数	五口二位 (5/2)													
	使用流体	空气													
	压力范围	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)													
	有效断面积	18 mm <sup>2</sup>													
	使用温度	0 ~ 60 °C													
重量	300 g														
<b>订购标示：</b>															
<div style="border: 1px solid black; border-radius: 15px; padding: 5px; display: inline-block;">訂購標示</div>															
<h2>H-5-1/4-S-2-22</h2>															
<b>1 型式</b> <b>2 方口數</b> <b>3 口徑</b>	<b>4 頭部型狀</b> <table border="1" style="margin-left: 20px;"> <tr> <td>S</td> <td>短柄</td> <td></td> </tr> <tr> <td>L</td> <td>長柄</td> <td></td> </tr> </table>	S	短柄		L	長柄									
S	短柄														
L	長柄														
	<b>5 顏色</b> <table border="1" style="margin-left: 20px;"> <tr> <td>2</td> <td>黑</td> </tr> <tr> <td>3</td> <td>綠</td> </tr> <tr> <td>4</td> <td>紅</td> </tr> </table>	2	黑	3	綠	4	紅								
2	黑														
3	綠														
4	紅														
	<b>6 安裝直徑</b> <table border="1" style="margin-left: 20px;"> <tr> <td>φ 22</td> </tr> <tr> <td>φ 30</td> </tr> </table>	φ 22	φ 30												
φ 22															
φ 30															

# 手鈕作動閥 (G1/4)



<b>产品名称：</b> 手鈕作動閥(G1/4)																													
<b>产品型号：</b> P-5-1/4-F-2-22																													
<b>产品介绍：</b> 产品型号：P-5-1/4-F-2-22 配管口径尺寸：G1/4 使用压力范围：1.5 ~ 8 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆5/2 滾輪作動閥，五口二位置。																													
<b>详细规格：</b>	<table border="1"> <tr> <td>接管口径</td> <td>G 1/4</td> </tr> <tr> <td>位置数</td> <td>五口二位 (5/2)</td> </tr> <tr> <td>使用流体</td> <td>空气</td> </tr> <tr> <td>压力范围</td> <td>1.5 ~ 8 kgf/cm<sup>2</sup> (0.15 ~ 0.8 MPa)</td> </tr> <tr> <td>有效断面积</td> <td>18 mm<sup>2</sup></td> </tr> <tr> <td>使用温度</td> <td>0 ~ 60 °C</td> </tr> <tr> <td>重量</td> <td>300 g</td> </tr> </table>	接管口径	G 1/4	位置数	五口二位 (5/2)	使用流体	空气	压力范围	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)	有效断面积	18 mm <sup>2</sup>	使用温度	0 ~ 60 °C	重量	300 g														
接管口径	G 1/4																												
位置数	五口二位 (5/2)																												
使用流体	空气																												
压力范围	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)																												
有效断面积	18 mm <sup>2</sup>																												
使用温度	0 ~ 60 °C																												
重量	300 g																												
<b>订购标示：</b>	<div style="text-align: center;"> <p><b>訂購標示</b></p> <p><b>P-5-1/4-F-2-22</b></p> <p>1 2 3 4 5 6</p> </div> <div style="display: flex; justify-content: space-around;"> <div style="width: 30%;"> <p><b>1 型式</b></p> <p><b>2 方口數</b></p> <p><b>3 口徑</b></p> </div> <div style="width: 30%;"> <p><b>4 頭部型狀</b></p> <table border="1" style="width: 100%;"> <tr> <td>F</td> <td>平頭</td> <td></td> </tr> <tr> <td>P</td> <td>凸頭</td> <td></td> </tr> <tr> <td>M</td> <td>蘑菇</td> <td></td> </tr> <tr> <td>MX</td> <td>大蘑菇</td> <td></td> </tr> <tr> <td>L</td> <td>有停駐</td> <td></td> </tr> <tr> <td>K</td> <td>有停駐及鎖</td> <td></td> </tr> </table> <p>註：L、K型之頭部材質為塑膠</p> </div> <div style="width: 30%;"> <p><b>5 顏色</b></p> <table border="1" style="width: 100%;"> <tr> <td>2</td> <td>黑</td> </tr> <tr> <td>3</td> <td>綠</td> </tr> <tr> <td>4</td> <td>紅</td> </tr> <tr> <td>6</td> <td>藍</td> </tr> </table> <p><b>6 安裝直徑</b></p> <table border="1" style="width: 100%;"> <tr> <td>φ 22</td> </tr> <tr> <td>φ 30</td> </tr> </table> </div> </div>	F	平頭		P	凸頭		M	蘑菇		MX	大蘑菇		L	有停駐		K	有停駐及鎖		2	黑	3	綠	4	紅	6	藍	φ 22	φ 30
F	平頭																												
P	凸頭																												
M	蘑菇																												
MX	大蘑菇																												
L	有停駐																												
K	有停駐及鎖																												
2	黑																												
3	綠																												
4	紅																												
6	藍																												
φ 22																													
φ 30																													

# 手鈕作動閥 (G1/8)



产品名称：手鈕作動閥(G1/8)															
产品型号：H-5-1/8-S-2-22															
产品介绍：产品型号：H-5-1/8-S-2-22 配管口径尺寸：G1/8 使用压力范围：1.5 ~ 8 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆5/2 滾輪作動閥，五口二位置。															
详细规格：	接管口径	G 1/8													
	位置数	五口二位 (5/2)													
	使用流体	空气													
	压力范围	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)													
	有效断面积	12 mm <sup>2</sup>													
	使用温度	0 ~ 60 °C													
	重量	100 g													
	订购标示： <div style="text-align: center; margin-top: 10px;"> <h2 style="margin: 0;">訂購標示</h2> <h3 style="margin: 0;">H-5-1/8-S-2-22</h3> <div style="display: flex; justify-content: space-around; margin: 5px 0;"> <span>1</span><span>2</span><span>3</span><span>4</span><span>5</span><span>6</span> </div> <div style="display: flex; justify-content: space-between; margin: 10px 0;"> <div style="width: 30%;"> <p>1 型式</p> <p>2 方口數</p> <p>3 口徑</p> </div> <div style="width: 30%;"> <p>4 頭部型狀</p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td style="padding: 5px;">S</td> <td style="padding: 5px;">短柄</td> <td style="padding: 5px;"></td> </tr> <tr> <td style="padding: 5px;">L</td> <td style="padding: 5px;">長柄</td> <td style="padding: 5px;"></td> </tr> </table> </div> <div style="width: 30%;"> <p>5 顏色</p> <table border="1" style="width: 100%; text-align: center;"> <tr><td style="padding: 5px;">2</td><td style="padding: 5px;">黑</td></tr> <tr><td style="padding: 5px;">3</td><td style="padding: 5px;">綠</td></tr> <tr><td style="padding: 5px;">4</td><td style="padding: 5px;">紅</td></tr> </table> <p>6 安裝直徑</p> <table border="1" style="width: 100%; text-align: center;"> <tr><td style="padding: 5px;">φ 22</td></tr> <tr><td style="padding: 5px;">φ 30</td></tr> </table> </div> </div> </div>		S	短柄		L	長柄		2	黑	3	綠	4	紅	φ 22
S	短柄														
L	長柄														
2	黑														
3	綠														
4	紅														
φ 22															
φ 30															

# 手鈕作動閥 (G1/8)



产品名称：	手鈕作動閥(G1/8)																													
产品型号：	P-5-1/8-F-2-22																													
产品介绍：	产品型号：P-5-1/8-F-2-22 配管口径尺寸：G1/8 使用压力范围：1.5 ~ 8 kgf/cm <sup>2</sup> 最大耐用压力：10 kgf/cm <sup>2</sup> ☆5/2 滚轮作動閥，五口二位。																													
详细规格：	接管口径	G 1/8																												
	位置数	五口二位 (5/2)																												
	使用流体	空气																												
	压力范围	1.5 ~ 8 kgf/cm <sup>2</sup> (0.15 ~ 0.8 MPa)																												
	有效断面积	12 mm <sup>2</sup>																												
	使用温度	0 ~ 60 °C																												
	重量	100 g																												
订购标示：	<div style="text-align: center;"> <h3>訂購標示</h3> <h2>P-5-1/8-F-2-22</h2> <p>1 2 3 4 5 6</p> </div> <div style="display: flex; justify-content: space-around;"> <div style="width: 30%;"> <p><b>1 型式</b></p> <p><b>2 方口數</b></p> <p><b>3 口徑</b></p> </div> <div style="width: 30%;"> <p><b>4 頭部型狀</b></p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td>F</td> <td>平頭</td> <td></td> </tr> <tr> <td>P</td> <td>凸頭</td> <td></td> </tr> <tr> <td>M</td> <td>蘑菇</td> <td></td> </tr> <tr> <td>MX</td> <td>大蘑菇</td> <td></td> </tr> <tr> <td>L</td> <td>有停駐</td> <td></td> </tr> <tr> <td>K</td> <td>有停駐及鎖</td> <td></td> </tr> </table> <p>註：L、K型之頭部材質為塑膠</p> </div> <div style="width: 30%;"> <p><b>5 顏色</b></p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td>2</td> <td>黑</td> </tr> <tr> <td>3</td> <td>綠</td> </tr> <tr> <td>4</td> <td>紅</td> </tr> <tr> <td>6</td> <td>藍</td> </tr> </table> <p><b>6 安裝直徑</b></p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td>φ 22</td> </tr> <tr> <td>φ 30</td> </tr> </table> </div> </div>		F	平頭		P	凸頭		M	蘑菇		MX	大蘑菇		L	有停駐		K	有停駐及鎖		2	黑	3	綠	4	紅	6	藍	φ 22	φ 30
F	平頭																													
P	凸頭																													
M	蘑菇																													
MX	大蘑菇																													
L	有停駐																													
K	有停駐及鎖																													
2	黑																													
3	綠																													
4	紅																													
6	藍																													
φ 22																														
φ 30																														