

薄型油压缸



产品名称：薄型油压缸												
产品型号：HJB, HJQ												
产品介绍：产品型号：HJB, HJQ 配管口径尺寸：PT1/4, PT3/8 使用压力范围：140 kgf/cm ² 缸管材质：碳钢 ☆薄型油压缸比一般油压缸较节省空间，相当适用于小型机械或空间受到限制的场所。												
详细规格：	作动方式		双动型									
	气缸内径(mm)		φ 32	φ 40	φ 50	φ 63	φ 80					
	标准行程(mm)		5 ~ 50									
	使用流体		已滤清之标准液压油									
	缸管材质		碳钢									
	使用压力范围		3 ~ 140 kgf/cm ²									
	使用速度范围		8 ~ 100 mm/sec									
	使用温度范围		-10 ~ +60 °C									
1.直接安装，不需其它配件，降低成本。 2.标准化规格，外型美观坚固，使用寿命长。 3.轴向.侧向油路板型，免配管提升整体美观。												
其它说明：单位 (m/m)												
型式	缸径	标准行程										
		5	10	15	20	25	30	35	40	45	50	
HJB	φ 32	●	●	●	●	●	●	—	—	—	—	
	φ 40	●	●	●	●	●	●	—	●	—	●	
	φ 50	●	●	●	●	●	●	—	●	—	●	
	φ 63	●	●	●	●	●	●	—	●	—	●	
	φ 80	●	●	●	●	●	●	—	●	—	●	
HJQ	φ 32	—	●	—	●	—	●	—	—	—	—	
	φ 40	—	●	—	●	—	●	—	●	—	●	
	φ 50	—	●	—	●	—	●	—	●	—	●	
	φ 63	—	●	—	●	—	●	—	●	—	●	
(●)为标准行程 (—)为非标准行程，可另外订制												