Electric High Pressure Pipe Cleaner



1.1/2" (40 mm) to 6" (150 mm).

This machine can be used to clean and uinblock all types of pipes most diameters of pipe obstructed by grease or friable materials such as grease, silt, soap, sand, clay, etc. as well as ice plugs.

ADVANTAGES:

EASY TO USE: All that is required is to guide the lightweight, flexible hose into the pipe by hand. It will then force its way through all obstructions. As it is extracted, the back-jets of the nozzle clean and rinse the walls of the pipe, allowing the pipe to flow freely once more.

POWERFUL AND ENDURING: 140 bar – 11 l/min. Radial pump with brass head and 3 high density ceramic pistons providing a four-fold increase in service life. It's slow operating speed (1440 rpm) allows it to run continuously for several hours at a time (4 hours) without the risk of overheating.

COMPLETE: high pressure pipe cleaner is supplied with 9 accessories.

POWER SUPPLY: The cleaner is powered at 220V, allowing it to be used on site or in the home. It's low power requirement (3000 W) allows it to be operated from a 15A line and aven a 10 kW generator set.

STURDY: reinforced hose.

VERY MANOEUVRABLE: Its two large diameter wheels allow it to draw from a tank.

VERY SAFE: This cleaner is fitted with a timed stop system. If left without working for 15 seconds, it shuts down and automatically restarts the moment the guin or the pedal is operated again.

PRATICAL: The two 10 m long hoses allow the cleaner to be used in places that are inaccessible to the machine (stairs, confined spaces, etc.).

FAST: When used as a cleaner, the 140 bar water pressure and flow rate of 660 l/h ensure a fast, efficient cleaning action. Using a rotary nozzle will significantly increase the impact force.

Supplied with: - 1 pipe cleaning hose, 1/4" diameter, 40 m long (without nozzle), - 1 stainless steel 3-jet nozzle (without front jet), - 1 stainless steel 4-jet nozzle (with front jet), - 1 standard stainless steel traction-effect rotary nozzle with brass bush, - 2 high pressure hoses, 10 m long, - 1 operating pedal, - 1 gun with double spray lance and free hand high/low pressure control.

DIMENSIONS MM	PRESSSURE BAR	MOTOR RATING	MAX. TEMPERATURE °C	PUMP FLOWRATE L/MIN	DRILLING SPEEDS RPM	REEL CAPACITY M	KG	REF
750 X 430 X 880	140	3 KW - 15 A	50	11	1440	40	63,500	293260