

## 2518 : Eurostem® II portable 14.4 V electric bending machine



### ADVANTAGES:

**NEW BATTERY: More powerful. Two times more bends. 20 % faster.**

Bending radius in accordance with French standard EN 1057. Bends up to 180°. Ideal of small and medium-sized jobs. Very sturdy speed reducer. Mobile hook for easily pipe placing and removal. **Maximum capacity:** - Hard copper, locksmith's and hydraulic pipes: Ø 10 to 28 mm, wall thickness 1 to 1.5 mm. - Stainless steel pipes: Ø 10 to 22 mm, wall thickness 1 mm Ø 28 mm, wall thickness 1.2 mm. - PEX/AL/PEX pipes: Ø 14 to 32 mm.

**Motor drive:** - 14.4 V – 2.4 Ah battery. - Bending speed: 0 to 4 rpm.

**Supplied in a box with a charger and 2 long-life batteries.**

\* For PEX/AL/PEX pipes.

VOLTAGE V	FORMERS Ø	COUNTER FORMER Ø	KG	REF
14,4	12 - 14 - 16 - 18 - 22 mm	12/15 - 14/16 - 18/22 mm	16,400	251800
14,4	12 - 15 - 18 - 22 mm	12/15 - 18/22 mm	15,000	251805
14,4	16 - 20 - 26 - 32 mm	14/16 - 20 - 26 - 32 mm	15,000	251806*
14,4	15 - 22 - 28 mm	12/15 - 18/22 - 28 mm	15,000	251845
14,4	15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	251846
14,4	1/2 - 5/8 - 3/4 - 7/8"	1/2 - 5/8 - 3/4 - 7/8"	14,000	251850

## 2518 : Eurostem® II Portable 230 V electric bending machine



Bending radius in accordance with French standard NF 1057. Bends up to 180°. Ideal of working with small and medium weight pipes. Very sturdy speed reducer. Mobile hook for easily pipe placing and removal.

**Maximum capacity:** - Hard copper, locksmith's and hydraulic pipes: Ø 10 to 28 mm, wall thickness 1 to 1.5 mm. - Stainless steel pipes: Ø 10 to 22 mm, wall thickness 1 mm Ø 28 mm, wall thickness 1.2 mm. - PEX/AL/PEX pipes: Ø 14 to 32 mm.

**Motor drive:** - 230 V - 50/60 Hz - 550 W. - Bending speed: 0 to 3 rpm.

**Supplied in a box.**

\* For PEX/AL/PEX pipes

VOLTAGE V	FORMERS Ø	COUNTER FORMER Ø	KG	REF
230	12 - 14 - 16 - 18 - 22 mm	12/15 - 14/16 - 18/22 mm	14,170	251802
230	12 - 15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	251807
230	16 - 20 - 26 - 32 mm	14/16 - 26 - 20 - 32 mm	15,000	251808*
230	15 - 22 - 28 mm	12/15 - 18/22 - 28 mm	15,000	251847
230	15 - 18 - 22 mm	12/15 - 18/22 mm	14,000	251848
230	1/2 - 5/8 - 3/4 - 7/8"	1/2 - 5/8 - 3/4 - 7/8"	14,000	251852

2518 : Formers and counter-formers for Eurostem® II



\* For PEX/AL/PEX pipes

\*\* For stainless steel pipes Ø 28 x 1.2 mm

TYPE	PIPE O.D. "	PIPE O.D. MM	BENDING RADIUS	KG	REF
Formers and counter-former	-	10	40	0,260	251810
Former	-	12	45	0,220	251812
Former	-	14	50	0,290	251814
Former	-	15	55	0,325	251815
Former	-	16	60	0,380	251816
Former	-	18	70	0,590	251818
Formers and counter-former	-	20	77	0,930	251820
Former	-	22	77	0,710	251822
Formers and counter-former	-	25	98	1,720	251825
Formers and counter-former	-	26	98	1,700	251826*
Formers and counter-former	-	28	98	1,560	251828
Formers and counter-former	-	28	112	1,820	251829**
Formers and counter-former	-	32	112	1,620	251831*
Formers and counter-former	3/8	-	40	0,270	251860
Former	1/2	-	45	0,240	251863
Former	5/8	-	55	0,320	251866
Former	3/4	-	70	0,600	251869
Former	7/8	-	77	0,690	251872
Formers and counter-former	1.1/8	-	98	1,600	251879
Counter-form	-	12/15	-	0,055	251832
Counter-form	-	14/16	-	0,065	251833
Counter-form	-	18/22	-	0,085	251834
Counter-form	1/2 - 5/8	-	-	0,050	251882
Counter-form	3/4 - 7/8	-	-	0,080	251883

**2518 : Concentric radius formers for Eurostem® II**



Ø MM	BENDING RADIUS	KG	REF
12	75	0,410	251835
14	80	0,580	251836
16	90	0,780	251837
18	105	0,960	251838
22	120	1,380	251839

**2518 : Battery and charger for Eurostem® II**



VOLTAGE	KG	REF
0,970	Battery 14,4 V - 2,4 Ah Ni-Cd	253242
1,030	230 V Battery charger - for 14,4 V battery - 2,4 Ah Ni-Cd	253243

**2518 : Tripod for Eurostem® II**



KG	REF
6,400	251809