

1375 : Phenix IIB portable electric threading machine



**ADVANTAGES :**

**COMPACT AND STRONG:** Ideal for use on site, in the workshop and in restricted spaces. Very reliable singlephase universal 750 W motor (220 V – 50/60 Hz or 115 V – 50/60 Hz).

**GEARED REVERSE:** for a quick return.

Heads can also be used with manual threaders.

**Capacity: Steel:** RIGHT BSPT, LEFT BSPT , NPT : Ø 1/8" - 2" (2 1/2" - 4" with adaptor) ISO (conduit) : M 16 to M 32 – Pitch 1.5. **Stainless steel:** RIGHT BSPT : Ø 3/8" - 1 1/4". LEFT BSPT : Ø 1/2" to 1". NPT: Ø 1/2" to 1" ISO (conduit) M 16 to M 32 – Pitch 1.5.

Supplied in a plastic case complete with: - 1 blocking vice, - 1 reducer for octagonal heads 1/8" to 1 1/4".

DESCRIPTION	POWER	VOLTAGE V	KG	REF
NO HEADS	750W - 50/60 HZ	230	16,140	137510
NO HEADS	750W - 50/60 HZ	115	18,200	137515
RIGHT BSPT : 1.1/2" - 2"	750W - 50/60 HZ	230	22,000	137520
RIGHT BSPT: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2"	750W - 50/60 HZ	230	22,600	137530
RIGHT BSPT: 1/2" - 3/4" - 1" - 1.1/4" - 1.1/2" - 2"	750W - 50/60 HZ	115	25,600	137535
BSPT DROITE : 1/2" - 3/4" - 1" - 1.1/4"	750W - 50/60 HZ	230	20,500	137540

1375 : Adaptor kit



Threads: RIGHT BSPT LEFT BSPP.

\* Supplied without threading machine 1375

DESCRIPTION	KG	REF
DIE-HEAD ONLY, WITH DIES	44,000	162500
COMPLETE 4" DIE-HEADS FOR 2" THREADING MACHINE (1375)*	53,000	162504
ADPATATEUR SEUL SANS MACHINE À FILETER ET SANS FILIÈRE	11,000	162512