

2529 : Viper® i10 manual hydraulic press fitting machine



ADVANTAGES:

PIVOTING HEAD: for ease of use in all situation.

ULTRA HIGH-PERFORMANCE HYDRAULIC SYSTEM, guaranteeing a perfect, long-lasting crimp.

AUDIBLE “CLICK” WHEN CRIMPING COMPLETE.

UNIVERSAL : suitable for crimping all connections currently available on the market (according to type of machine).

COMFORT OF USE : ergonomic and well balanced for effortless crimping, best weight-to-power ratio on market.

WIDE CHOICE OF CRIMPING JAWS : Virax has jaws for the majority of crimping systems available on the market.

Lightweight and ergonomic, can be operated with one hand

PER, PEX, PB, and PEX/AL/PEX pipes Ø 12 to 20 mm.

- 180° rotating head for working in any position, - Quick head opening and closing.

Supplied in a case (without inserts).

WARNING: *does not accept all insert profiles.*

DESCRIPTION	CASE DIMENSIONS MM	KG (MACHINE)	REF
VIPER® I 10	380 X 280 X 75	2,760	252900

2529 - 2532 : Inserts for models i10 / i11 / i20 / i21 / M20+ / M24



Lightweight. Compact. Very good value for money. Very high strength steel (33 HRC). Very precise crimping.

OFF CENTRED	12	TH	-	-	-	-	OK	OK	253265
STANDARD	14	TH	OK	OK	OK	OK	OK	OK	252902
OFF CENTRED	14	TH	-	-	-	-	OK	OK	253266
STANDARD	15	TH	OK	OK	OK	OK	OK	OK	252903
OFF CENTRED	15	TH	-	-	-	-	OK	OK	253267
STANDARD	16	TH	OK	OK	OK	OK	OK	OK	252904
OFF CENTRED	16	TH	-	-	-	-	OK	OK	253268
STANDARD	17	TH	OK	OK	OK	OK	OK	OK	252905
OFF CENTRED	17	TH	-	-	-	-	OK	OK	253269
STANDARD	18	TH	OK	OK	OK	OK	OK	OK	252906
OFF CENTRED	18	TH	-	-	-	-	OK	OK	253270
STANDARD	20	TH	OK	OK	OK	OK	OK	OK	252907
OFF CENTRED	20	TH	-	-	-	-	OK	OK	253271
STANDARD	25	TH	-	OK	OK	OK	OK	OK	252908
STANDARD	26	TH	-	OK	OK	OK	OK	OK	252909
STANDARD	32	TH	-	OK	OK	OK	OK	OK	252911
OFF CENTRED	14	U	-	-	-	-	OK	OK	253281
STANDARD	16	U	OK	OK	OK	OK	OK	OK	252915
OFF CENTRED	16	U	-	-	-	-	OK	OK	253272
STANDARD	18	U	-	-	-	-	OK	OK	252916
STANDARD	20	U	OK	OK	OK	OK	OK	OK	252917
OFF CENTRED	20	U	-	-	-	-	OK	OK	253273
STANDARD	25	U	-	OK	OK	OK	OK	OK	252918
STANDARD	32	U	-	-	-	-	OK	OK	252919
STANDARD	12	V	-	OK	OK	OK	OK	OK	252961
OFF CENTRED	12	V	-	-	-	-	OK	OK	253274
STANDARD	14	V	-	-	-	-	OK	OK	252966
OFF CENTRED	14	V	-	-	-	-	OK	OK	253275
STANDARD	15	V	-	OK	OK	OK	OK	OK	252962
OFF CENTRED	15	V	-	-	-	-	OK	OK	253276
STANDARD	16	V	-	OK	OK	OK	OK	OK	252967
OFF CENTRED	18	V	-	-	-	-	OK	OK	253278
STANDARD	18	V	-	OK	OK	OK	OK	OK	252963
STANDARD	22	V	-	OK	OK	OK	OK	OK	252964
STANDARD	28	V	-	OK	OK	OK	OK	OK	252965
OFF CENTRED	16	V	-	-	-	-	OK	OK	253277

2529 : Viper® i11 manual hydraulic press fitting machine



ADVANTAGES:

PIVOTING HEAD: for ease of use in all situation.

ULTRA HIGH-PERFORMANCE HYDRAULIC SYSTEM, guaranteeing a perfect, long-lasting crimp.

AUDIBLE “CLICK” WHEN CRIMPING COMPLETE.

UNIVERSAL : suitable for crimping all connections currently available on the market (according to type of machine).

COMFORT OF USE : ergonomic and well balanced for effortless crimping, best weight-to-power ratio on market.

WIDE CHOICE OF CRIMPING JAWS : Virax has jaws for the majority of crimping systems available on the market.

PER, PEX, PB, and PEX/AL/PEX pipes Ø 12 to 32 mm

Copper, stainless steel and mild steel pipes: Ø 12 to 28 mm

Lightweight and ergonomic.

- 180° rotating head for working in any position, - Quick head opening and closing.

Supplied in a case (without inserts) .

DESCRIPTION	CASE DIMENSIONS MM	KG (MACHINE)	REF
VIPER® I 11	515 X 235 X 75	2,850	252910

2529 - 2530 : Battery



TYPE	CHARACTERISTIC	V	AH	KG	REF
I20	1000 CHARGES ON 1 HOUR CHARGER, 1500 CHARGES ON 15 MINUTE CHARGER, RECHARGEABLE NI-CD	12	2,2	0,640	252923
I21/P20/P20+	1000 CHARGES ON 1 HOUR CHARGER, 1500 CHARGES ON 23 MINUTE CHARGER, RECHARGEABLE NI-MH	14,4	3	0,640	252932
P21/P21+	1000 CHARGES ON 1 HOUR CHARGER RECAHRGEABLE NI-MH	18	3	0,640	253023

2529 : Viper® i21 battery-powered hydraulic press fitting machine with 14.4 v (2.6 ah) Ni-Mh battery



ADVANTAGES :

PIVOTING HEAD: for ease of use in all situation.

ULTRA HIGH-PERFORMANCE HYDRAULIC SYSTEM, guaranteeing a perfect, long-lasting crimp.

AUDIBLE “CLICK” WHEN CRIMPING COMPLETE.

UNIVERSAL : suitable for crimping all connections currently available on the market (according to type of machine).

COMFORT OF USE : ergonomic and well balanced for effortless crimping, best weight-to-power ratio on market.

WIDE CHOICE OF CRIMPING JAWS : Virax has jaws for the majority of crimping systems available on the market.

Tools complying with CE standards and Tüv-GS.

PER, PEX, PB, and PEX/AL/PEX pipes Ø 12 to Ø 32 mm

Copper, stainless steel and mild steel pipes: Ø 12 to 28 mm

- 2-speed hydraulic system for faster crimping – Variable speed control within the trigger, - Quick, - Highly autonomous

- Ergonomic, - 180° rotating head, - Quick head, - End of crimping indicator, - Maintenance indicator lights after 20,000 crimping operations, - Battery charge indicator.

Supplied in a case complete with: - 14.4 V battery, - 1-hr. battery charger.

DESCRIPTION	CASE DIMENSIONS MM	KG (MACHINE)	REF
VIPER® I21	510 X 360 X 115	4,100	252925

2529 - 2530: Battery Charger



TYPE	CHARACTERISTIC	V	TIME OF LOADING	KG	REF
I20/I21 AND P20/P20+	STANDBY SYSTEM	12/14,4	1H	1,360	252926
I20/I21 AND P20/P20+	STANDBY SYSTEM	12/14,4	15/23 MIN	1,260	252929
I20/I21 AND P20/P20+	12 V OR 24 V CAR CIGARETTE LIGHTER PLUG	12/14,4	1H	0,520	252931
I20/I21 AND P20/P20+/P21/P21+	STANDBY SYSTEM	12/14,4/18	75 MIN	1,360	253024