

2208 : Drill bit for pipe-tapping machine



Ø MM	TYPE	KG	REF
20	FOR CAST-IRON PIPE	0,185	220820
25	FOR CAST-IRON PIPE	0,275	220825
32	FOR CAST-IRON PIPE	0,350	220532
40	FOR CAST-IRON PIPE	0,485	220840

2208 : Accessories for pipe-tapping machine



H MM	Ø MM	TYPE	Ø "	KG	REF
-	7	PILOT FOR PLASTIC PIPE	-	0,015	220807
-	20 - 25	SAW HOLDER WITH BIT FOR DRILLING PLASTIC PIPES	-	0,085	220852
-	32 - 40	SAW HOLDER WITH BIT FOR DRILLING PLASTIC PIPES	-	0,160	220853
50	20,6	HOLE SAW	13/16	0,050	220913
50	25,4	HOLE SAW	1	0,060	220916
50	31,7	HOLE SAW	1.1/4	0,087	220820
50	39,7	HOLE SAW	1.9/16	0,075	220995
-	-	SPACER	-	2,800	220851
-	-	ROQUETE Ø 1/2"	-	0,765	220871
-	-	17 MM RATCHET	-	0,070	220872
-	-	PIPE-TAPPING MACHINE (WITHOUT ACCESSORIES)	-	5,600	220874

2208 : Pipe-tapping machine



For forming 20, 25, 32 and 40 mm Ø. branch connections on cast iron or plastic water pipes under pressure. 11-point stepped spindle adjustment, to take account of the different valve heights.

Principle of operation : - The base of the machine is connected to a stop valve previously clamped onto the pipe. - The valve is opened and the drill inserted via the opening thus formed.

Supplied in a case complete with a 1/2" ratchet and 17 mm socket.

COMPOSITION	KG	REF
NO TOOLS	15,900	220875
20 - 25 - 32 - 40 MM Ø DRILL	17,200	220877
20 - 25 - 32 - 40 MM Ø DRILL BITS, 20 - 25 - 32 - 40 MM Ø SAWS, 20 - 25 SAW HOLDER WITH BIT FOR DRILLING PLASTIC, 32 - 40 MM SAW HOLDER WITH BIT FOR DRILLING PLASTIC	17,750	220870