


MAF401A / D / M series


AIR UNITS (Air / Mist / Micromist Filter)




Symbol:



A : 5 μ m



D : 0.3 μ m



M : 0.01 μ m

- MAF401A is designed for draining and removal of foreign matter. (Element : 5 μ m)
- MAF401D/M is designed for removal of foreign matter as well as oil mist (Element : 0.3 μ m / 0.01 μ m)

Specification:

Model	MAF401A/D/M		
Bore No.	8A	10A	15A
Port size	PT 1/4	PT 3/8	PT 1/2
Medium	Air		
Operating pressure range	0~15 kgf/cm ² (0~1.5 MPa)		
Proof pressure	20 kgf/cm ² (2 MPa)		
Ambient temperature	-5~+60°C (No freezing)		
Filtration	5 μ m, 0.3 μ m, 0.01 μ m		
Weight	480 g		

※ Standard unit contains semi-auto-drain function when operating pressure below 0.5 kgf/cm²

Order example:

MAF401D — 8A — □ — B — BSP

MODEL

BORE SIZE

8A: PT 1/4
10A: PT 3/8
15A: PT 1/2

C Type Bracket

D: auto drain valve

PORT THREAD
Blank: PT thread
BSP: BSP thread
NPT: NPT thread

FILTRATION
A: 5 μ m
D: 0.3 μ m
M: 0.01 μ m

Option accessories

C type bracket

